

SPECIFICATIONS

MODEL

1180A

Type :	Two Channel audio power amplifier
Power Output :	550 Watts per channel 8 ohms 900 Watts per channel 4 ohms 1400 Watts bridged mono 8 ohms
Control and Indicators :	AC mains power switch, power on LED indicator. Each channel has individual level controls, signal/clip indicators, balanced/unbalanced inputs. Ground lift switch.
Turn-On Delay :	3 second, solid state activated
Thermal Protection :	Thermal sensor activates channel shut down at 95°C
DC Protection :	DC sensor activates channel shut down if a DC condition exists.
Cooling :	High efficiency, convection cooled with "Venturi Style" fan assist (Option) providing utilizing massive heat sink extrusions
Damping Factor	1000:1 at 1kHz
Freq. Response:	Plus/minus .25dB 20Hz to 20kHz
Distortion:	No more than 0.1%THD
Hum and Noise:	110dB
Input Sensitivity:	Selectable, .775v,1.0v,1.5v, shipped at 1.0v for rated output
Input Impedance:	15k ohms nominal, Balanced and Unbalanced inputs
Input Connectors:	(2) ¼" phone jacks (Unbalanced), (2) XLR (Balanced)
Output Connectors:	Dual 5-way binding posts
Power Input:	1700W 100/240 VAC 50/60Hz
Dimensions:	5 ¼"H , 19"W , 13" D
Weight:	20 Kg

