

## Specifications

Type:	Two channel audio power amplifier
Gain:	26 dB (each channel)
Continuous Average Power Output	75 watts per channel at 8 ohms 100 watts per channel at 4 ohms 180 watts at Bridged mono at 8 ohms.
Frequency Response:	Plus/Minus 0.5dB 20Hz-20kHz
Distortion:	No more than 0.25% THD or IM, 0.01W to rated power, 20Hz to 20kHz (typically 0.02%)
Hum and Noise:	101dB below rated output (unweighted 20KHz bandwidth)
Input Sensitivity:	1.6V RMS for rated output
Input Impedance:	15K ohms, nominal
Input Connector:	(2) 1/4-inch phone jacks and XLR jacks. (unbalanced and balanced)
Output Connectors:	Dual 5-way binding posts
Controls & Indicators:	(Front Panel) AC main power switch, Power-on LED indicator, Signal on LED indicator Clip LED indicator × 2pcs Channel One and Two level controls Monitor jacks 2 pcs
Power:	110-120VAC/60Hz } switchable 220-240VAC/50Hz } 30W (idle), 300W (maximum)
Dimensions:	1-3/4''H (4.4cm) 19''W (48.3cm) 11.9'' (30.2cm) behind panel 13'' (32.5cm) overall
Weight:	16.2 lbs (7.3 kg)