

Specifications

Model 280A

Type	Two Channel Audio Power Amplifier
Power Output	75 Watts per channel into 8 ohms 100 Watts per channel into 8 ohms 180 Watts bridged mono into 8 ohms
Control/Indicators	AC mains power switch, power on LED indicator. Ground lift switch. Bridge/Stereo switch. Each channel has individual level controls, Signal/Clip indicators, and balanced/unbalanced Inputs. Two front panel headphone jacks.
Turn-On Delay	3 second, solid-state activated
Damping Factor	250:1 at 1kHz
Freq. Response	Plus/Minus 0.5db 20Hz to 20kHz
Distortion	No more than 0.25%THD
Hum and Noise	101 db below rated output
Input Sensitivity	1.0Vrms for rated output
Input Impedance	15k ohms nominal, Balanced and Unbalanced inputs
Output Connectors	Dual 5-way binding posts
Power Input	100/240Vac 50/60 Hz, 300 watts
Wasted Heat (BTU/HR) (Calculated)	320 BTU/HR @ 75wpc rms 8 ohms both channels driven @ 50% duty cycle 380 BTU/HR @ 100wpc rms 4 ohms both channels driven @ 50% duty cycle
Dimensions	1 3/4" H, 19" W, 13" D
Weight	7.3kg

